

## AMENDED CLAIMS

[Received by the International Bureau on 22 April 2004 (22.04.04):  
original claims 1 to 7 replaced by amended claims 1 to 5 (1 page)]

1. Equipment for change of rotary gobos comprising a carrier disc  
5 provided with circular apertures (9) allowing for lighting of gobos and  
furnished with resilient holding means to support interchangeable segments  
with the gobos, **characterised in**, that each segment (2) is provided with  
a lamella (3) for attachment in the holding means and with means for setting  
the segment (2) on the carrier disc (1).
- 10
2. Equipment for a change of rotary gobos according to claim 1, **characterised  
in**, that the holding means comprise a system of flexible fingers (10) in a fan-  
shaped arrangement, the fingers (10) being at inside ends fixed to the carrier  
disc (1) and on the outside free ends adapted to allow for insertion of the  
15 segment lamellas (3) between the fingers (10) and the carrier disc (1).
3. Equipment for a change of rotary gobos according to claim 2,  
**characterised in**, that the fingers (10) are at their inside ends integrated into  
one unit, while the number of fingers (10) within this unit corresponds to the  
20 number of segments (2) to be supported by the carrier disc (1).
4. Equipment for a change of rotary gobos according to claim 1,  
**characterised in**, that each segment (2) is provided with a bearing supporting  
a driver (6) with a gobo, the bearing inside ring being provided for by the  
25 driver (6) outer rim and the bearing outside ring (5) being attached to the  
segment lamella (3) by dismountable-connection means, while the driver (6)  
comprise a flange (7) with a spur toothing.
5. Equipment for a change of rotary gobos according to claim 1 or 4,  
30 **characterised in**, that the means for setting the segment (2) on the carrier  
disc (1) comprise dismountable-connection means for attachment of the  
gobo bearing outer ring (5) on the lamella (3).